

# Generalized Morphisms For CAP

Implementations of generalized morphisms for the CAP project

2017.09.09

9 September 2017

**Sebastian Gutsche**

**Sebastian Posur**

**Sebastian Gutsche**

Email: [gutsche@mathematik.uni-siegen.de](mailto:gutsche@mathematik.uni-siegen.de)

Homepage: <http://www.uni-siegen.de/fb6/rmi/>

Address: Department Mathematik

Universität Siegen

Walter-Flex-Straße 3

57068 Siegen

Germany

**Sebastian Posur**

Email: [sebastian.posur@uni-siegen.de](mailto:sebastian.posur@uni-siegen.de)

Homepage: <http://www.uni-siegen.de/fb6/rmi/>

Address: Department Mathematik

Universität Siegen

Walter-Flex-Straße 3

57068 Siegen

Germany

# Contents

<b>1</b>	<b>Generalized Morphism Category</b>	<b>4</b>
1.1	GAP Categories . . . . .	4
1.2	Attributes . . . . .	4
1.3	Operations . . . . .	6
1.4	Properties . . . . .	6
1.5	Convenience methods . . . . .	7
<b>2</b>	<b>Generalized Morphism Category by Cospans</b>	<b>9</b>
2.1	GAP Categories . . . . .	9
2.2	Properties . . . . .	9
2.3	Attributes . . . . .	9
2.4	Operations . . . . .	11
2.5	Constructors . . . . .	11
2.6	Constructors of lifts of exact functors and natural (iso)morphisms . . . . .	12
<b>3</b>	<b>Generalized Morphism Category by Spans</b>	<b>13</b>
3.1	GAP Categories . . . . .	13
3.2	Properties . . . . .	13
3.3	Attributes . . . . .	13
3.4	Operations . . . . .	15
3.5	Constructors . . . . .	15
<b>4</b>	<b>Generalized Morphism Category by Three Arrows</b>	<b>17</b>
4.1	GAP Categories . . . . .	17
4.2	Properties . . . . .	17
4.3	Attributes . . . . .	18
4.4	Operations . . . . .	19
4.5	Constructors . . . . .	19
<b>5</b>	<b>Conversion functors for generalized morphisms</b>	<b>21</b>
5.1	Functors from Cospans . . . . .	21
5.2	Functors from Spans . . . . .	21
5.3	Functors from Three Arrows . . . . .	22
<b>6</b>	<b>Serre Quotients Subcategory</b>	<b>23</b>
6.1	implementation . . . . .	23

<b>7</b>	<b>Serre Quotients</b>	<b>24</b>
7.1	General operations . . . . .	24
7.2	Serre quotients by cospans . . . . .	27
7.3	Serre Quotients by Spans . . . . .	28
7.4	Serre Quotients modeled by three arrows . . . . .	29
<b>8</b>	<b>Serre Quotients Functors</b>	<b>32</b>
8.1	Functors . . . . .	32
<b>9</b>	<b>Examples and Tests</b>	<b>33</b>
9.1	Basic Commands . . . . .	33
9.2	Intersection of Nodal Curve and Cusp . . . . .	33
9.3	Sweep . . . . .	34

# Chapter 1

## Generalized Morphism Category

Let  $\mathbf{A}$  be an abelian category. We denote its generalized morphism category by  $\mathbf{G}(\mathbf{A})$ .

### 1.1 GAP Categories

#### 1.1.1 IsGeneralizedMorphismCategoryObject (for IsCapCategoryObject)

- ▷ `IsGeneralizedMorphismCategoryObject(object)` (filter)  
**Returns:** true or false  
The GAP category of objects in the generalized morphism category.

#### 1.1.2 IsGeneralizedMorphism (for IsCapCategoryMorphism)

- ▷ `IsGeneralizedMorphism(object)` (filter)  
**Returns:** true or false  
The GAP category of morphisms in the generalized morphism category.

### 1.2 Attributes

#### 1.2.1 UnderlyingHonestObject (for IsGeneralizedMorphismCategoryObject)

- ▷ `UnderlyingHonestObject(a)` (attribute)  
**Returns:** an object in  $\mathbf{A}$   
The argument is an object  $a$  in the generalized morphism category. The output is its underlying honest object

#### 1.2.2 DomainOfGeneralizedMorphism (for IsGeneralizedMorphism)

- ▷ `DomainOfGeneralizedMorphism(alpha)` (attribute)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{A}}(d, a)$   
The argument is a generalized morphism  $\alpha : a \rightarrow b$ . The output is its domain  $d \hookrightarrow a \in \mathbf{A}$ .

### 1.2.3 Codomain (for IsGeneralizedMorphism)

▷ `Codomain(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{A}}(b, c)$

The argument is a generalized morphism  $\alpha : a \rightarrow b$ . The output is its codomain  $b \rightarrow c \in \mathbf{A}$ .

### 1.2.4 AssociatedMorphism (for IsGeneralizedMorphism)

▷ `AssociatedMorphism(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{A}}(d, c)$

The argument is a generalized morphism  $\alpha : a \rightarrow b$ . The output is its associated morphism  $d \rightarrow c \in \mathbf{A}$ .

### 1.2.5 DomainAssociatedMorphismCodomainTriple (for IsGeneralizedMorphism)

▷ `DomainAssociatedMorphismCodomainTriple(alpha)` (attribute)

**Returns:** a triple of morphisms in  $\mathbf{A}$

The argument is a generalized morphism  $\alpha : a \rightarrow b$ . The output is a triple  $(d \hookrightarrow a, d \rightarrow c, b \rightarrow c)$  consisting of its domain, associated morphism, and codomain.

### 1.2.6 HonestRepresentative (for IsGeneralizedMorphism)

▷ `HonestRepresentative(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{A}}(a, b)$

The argument is a generalized morphism  $\alpha : a \rightarrow b$ . The output is the honest representative in  $\mathbf{A}$  of  $\alpha$ , if it exists, otherwise an error is thrown.

### 1.2.7 GeneralizedInverse (for IsCapCategoryMorphism)

▷ `GeneralizedInverse(alpha)` (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, a)$

The argument is a morphism  $\alpha : a \rightarrow b \in \mathbf{A}$ . The output is its generalized inverse  $b \rightarrow a$ .

### 1.2.8 IdempotentDefinedBySubobject (for IsCapCategoryMorphism)

▷ `IdempotentDefinedBySubobject(alpha)` (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, b)$

The argument is a subobject  $\alpha : a \hookrightarrow b \in \mathbf{A}$ . The output is the idempotent  $b \rightarrow b \in \mathbf{G}(\mathbf{A})$  defined by  $\alpha$ .

### 1.2.9 IdempotentDefinedByFactorobject (for IsCapCategoryMorphism)

▷ `IdempotentDefinedByFactorobject(alpha)` (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, b)$

The argument is a factorobject  $\alpha : b \rightarrow a \in \mathbf{A}$ . The output is the idempotent  $b \rightarrow b \in \mathbf{G}(\mathbf{A})$  defined by  $\alpha$ .

### 1.2.10 UnderlyingHonestCategory (for IsCapCategory)

▷ UnderlyingHonestCategory( $C$ ) (attribute)

**Returns:** a category

The argument is a generalized morphism category  $C = \mathbf{G}(\mathbf{A})$ . The output is  $\mathbf{A}$ .

## 1.3 Operations

### 1.3.1 GeneralizedMorphismFromFactorToSubobject (for IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ GeneralizedMorphismFromFactorToSubobject( $beta, alpha$ ) (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(c, a)$

The arguments are a factorobject  $\beta : b \rightarrow c$ , and a subobject  $\alpha : a \hookrightarrow b$ . The output is the generalized morphism from the factorobject to the subobject.

### 1.3.2 CommonRestriction (for IsList)

▷ CommonRestriction( $L$ ) (operation)

**Returns:** a list of generalized morphisms

The argument is a list  $L$  of generalized morphisms by three arrows having the same source. The output is a list of generalized morphisms by three arrows which is the common restriction of  $L$ .

### 1.3.3 ConcatenationProduct (for IsList)

▷ ConcatenationProduct( $L$ ) (operation)

**Returns:** a generalized morphism

The argument is a list  $L = (\alpha_1, \dots, \alpha_n)$  of generalized morphisms (with same data structures). The output is their concatenation product, i.e., a generalized morphism  $\alpha$  with  $\text{UnderlyingHonestObject}(\text{Source}(\alpha)) = \bigoplus_{i=1}^n \text{UnderlyingHonestObject}(\text{Source}(\alpha_i))$ , and  $\text{UnderlyingHonestObject}(\text{Range}(\alpha)) = \bigoplus_{i=1}^n \text{UnderlyingHonestObject}(\text{Range}(\alpha_i))$ , and with morphisms in the representation of  $\alpha$  given as the direct sums of the corresponding morphisms of the  $\alpha_i$ .

## 1.4 Properties

### 1.4.1 IsHonest (for IsGeneralizedMorphism)

▷ IsHonest( $alpha$ ) (property)

**Returns:** a boolean

The argument is a generalized morphism  $\alpha$ . The output is true if  $\alpha$  admits an honest representative, otherwise false.

### 1.4.2 HasFullDomain (for IsGeneralizedMorphism)

▷ HasFullDomain( $alpha$ ) (property)

**Returns:** a boolean

The argument is a generalized morphism  $\alpha$ . The output is `true` if the domain of  $\alpha$  is an isomorphism, otherwise `false`.

### 1.4.3 HasFullCodomain (for IsGeneralizedMorphism)

▷ `HasFullCodomain( $\alpha$ )` (property)

**Returns:** a boolean

The argument is a generalized morphism  $\alpha$ . The output is `true` if the codomain of  $\alpha$  is an isomorphism, otherwise `false`.

### 1.4.4 IsSingleValued (for IsGeneralizedMorphism)

▷ `IsSingleValued( $\alpha$ )` (property)

**Returns:** a boolean

The argument is a generalized morphism  $\alpha$ . The output is `true` if the codomain of  $\alpha$  is an isomorphism, otherwise `false`.

### 1.4.5 IsTotal (for IsGeneralizedMorphism)

▷ `IsTotal( $\alpha$ )` (property)

**Returns:** a boolean

The argument is a generalized morphism  $\alpha$ . The output is `true` if the domain of  $\alpha$  is an isomorphism, otherwise `false`.

## 1.5 Convenience methods

This section contains operations which, depending on the current generalized morphism standard of the system and the category, might point to other Operations. Please use them only as convenience and never in serious code.

### 1.5.1 GeneralizedMorphismCategory (for IsCapCategory)

▷ `GeneralizedMorphismCategory( $\mathcal{C}$ )` (operation)

**Returns:** a category

Creates a new category of generalized morphisms. Might point to `GeneralizedMorphismCategoryByThreeArrows`, `GeneralizedMorphismCategoryByCospans`, or `GeneralizedMorphismCategoryBySpans`

### 1.5.2 GeneralizedMorphismObject (for IsCapCategoryObject)

▷ `GeneralizedMorphismObject( $A$ )` (operation)

**Returns:** an object in the generalized morphism category

Creates an object in the current generalized morphism category, depending on the standard

### 1.5.3 AsGeneralizedMorphism (for IsCapCategoryMorphism)

▷ `AsGeneralizedMorphism(phi)` (operation)

**Returns:** a generalized morphism

Returns the corresponding morphism to *phi* in the current generalized morphism category.

### 1.5.4 GeneralizedMorphism (for IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `GeneralizedMorphism(phi, psi)` (operation)

**Returns:** a generalized morphism

Returns the corresponding morphism to *phi* and *psi* in the current generalized morphism category.

### 1.5.5 GeneralizedMorphism (for IsCapCategoryMorphism, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `GeneralizedMorphism(iota, phi, pi)` (operation)

**Returns:** a generalized morphism

Returns the corresponding morphism to *iota*, *phi* and *psi* in the current generalized morphism category.

### 1.5.6 GeneralizedMorphismWithRangeAid (for IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `GeneralizedMorphismWithRangeAid(arg1, arg2)` (operation)

Returns a generalized morphism with range aid by three arrows or by span, or a generalized morphism by cospan, depending on the standard.

### 1.5.7 GeneralizedMorphismWithSourceAid (for IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `GeneralizedMorphismWithSourceAid(arg1, arg2)` (operation)

Returns a generalized morphism with source aid by three arrows or by cospan, or a generalized morphism by span, depending on the standard.



## Chapter 2

# Generalized Morphism Category by Cospans

### 2.1 GAP Categories

#### 2.1.1 `IsGeneralizedMorphismCategoryByCospansObject` (for `IsGeneralizedMorphismCategoryObject`)

▷ `IsGeneralizedMorphismCategoryByCospansObject(object)` (filter)

**Returns:** true or false

The GAP category of objects in the generalized morphism category by cospans.

#### 2.1.2 `IsGeneralizedMorphismByCospan` (for `IsGeneralizedMorphism`)

▷ `IsGeneralizedMorphismByCospan(object)` (filter)

**Returns:** true or false

The GAP category of morphisms in the generalized morphism category by cospans.

### 2.2 Properties

#### 2.2.1 `HasIdentityAsReversedArrow` (for `IsGeneralizedMorphismByCospan`)

▷ `HasIdentityAsReversedArrow(alpha)` (property)

**Returns:** true or false

The argument is a generalized morphism  $\alpha$  by a cospan  $a \rightarrow b \leftarrow c$ . The output is true if  $b \leftarrow c$  is congruent to an identity morphism, false otherwise.

### 2.3 Attributes

#### 2.3.1 `UnderlyingHonestObject` (for `IsGeneralizedMorphismCategoryByCospansObject`)

▷ `UnderlyingHonestObject(a)` (attribute)

**Returns:** an object in A

The argument is an object  $a$  in the generalized morphism category by cospans. The output is its underlying honest object.

### 2.3.2 Arrow (for IsGeneralizedMorphismByCospan)

▷ `Arrow(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{A}}(a, c)$

The argument is a generalized morphism  $\alpha$  by a cospan  $a \rightarrow b \leftarrow c$ . The output is its arrow  $a \rightarrow b$ .

### 2.3.3 ReversedArrow (for IsGeneralizedMorphismByCospan)

▷ `ReversedArrow(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{A}}(c, b)$

The argument is a generalized morphism  $\alpha$  by a cospan  $a \rightarrow b \leftarrow c$ . The output is its reversed arrow  $b \leftarrow c$ .

### 2.3.4 NormalizedCospanTuple (for IsGeneralizedMorphismByCospan)

▷ `NormalizedCospanTuple(alpha)` (attribute)

**Returns:** a pair of morphisms in  $\mathbf{A}$ .

The argument is a generalized morphism  $\alpha : a \rightarrow b$  by a cospan. The output is its normalized cospan pair  $(a \rightarrow d, d \leftarrow b)$ .

### 2.3.5 PseudoInverse (for IsGeneralizedMorphismByCospan)

▷ `PseudoInverse(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, a)$

The argument is a generalized morphism  $\alpha : a \rightarrow b$  by a cospan. The output is its pseudo inverse  $b \rightarrow a$ .

### 2.3.6 GeneralizedInverseByCospan (for IsCapCategoryMorphism)

▷ `GeneralizedInverseByCospan(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, a)$

The argument is a morphism  $\alpha : a \rightarrow b \in \mathbf{A}$ . The output is its generalized inverse  $b \rightarrow a$  by cospan.

### 2.3.7 IdempotentDefinedBySubobjectByCospan (for IsCapCategoryMorphism)

▷ `IdempotentDefinedBySubobjectByCospan(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, b)$

The argument is a subobject  $\alpha : a \hookrightarrow b \in \mathbf{A}$ . The output is the idempotent  $b \rightarrow b \in \mathbf{G}(\mathbf{A})$  by cospan defined by  $\alpha$ .

### 2.3.8 IdempotentDefinedByFactorobjectByCospan (for IsCapCategoryMorphism)

▷ `IdempotentDefinedByFactorobjectByCospan(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, b)$

The argument is a factorobject  $\alpha : b \twoheadrightarrow a \in \mathbf{A}$ . The output is the idempotent  $b \rightarrow b \in \mathbf{G}(\mathbf{A})$  by cospan defined by  $\alpha$ .

### 2.3.9 NormalizedCospan (for IsGeneralizedMorphismByCospan)

- ▷ `NormalizedCospan(alpha)` (attribute)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, b)$   
 The argument is a generalized morphism  $\alpha : a \rightarrow b$  by a cospan. The output is its normalization by cospan.

## 2.4 Operations

### 2.4.1 GeneralizedMorphismFromFactorToSubobjectByCospan (for IsCapCategoryMorphism, IsCapCategoryMorphism)

- ▷ `GeneralizedMorphismFromFactorToSubobjectByCospan(beta, alpha)` (operation)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(c, a)$   
 The arguments are a factorobject  $\beta : b \rightarrow c$ , and a subobject  $\alpha : a \hookrightarrow b$ . The output is the generalized morphism by cospan from the factorobject to the subobject.

## 2.5 Constructors

### 2.5.1 GeneralizedMorphismByCospan (for IsCapCategoryMorphism, IsCapCategoryMorphism)

- ▷ `GeneralizedMorphismByCospan(alpha, beta)` (operation)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, c)$   
 The arguments are morphisms  $\alpha : a \rightarrow b$  and  $\beta : c \rightarrow b$  in  $\mathbf{A}$ . The output is a generalized morphism by cospan with arrow  $\alpha$  and reversed arrow  $\beta$ .

### 2.5.2 GeneralizedMorphismByCospan (for IsCapCategoryMorphism, IsCapCategoryMorphism)

- ▷ `GeneralizedMorphismByCospan(alpha, beta, gamma)` (operation)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, d)$   
 The arguments are morphisms  $\alpha : a \leftarrow b$ ,  $\beta : b \rightarrow c$ , and  $\gamma : c \leftarrow d$  in  $\mathbf{A}$ . The output is a generalized morphism by cospan defined by the composition the given three arrows regarded as generalized morphisms.

### 2.5.3 GeneralizedMorphismByCospanWithSourceAid (for IsCapCategoryMorphism, IsCapCategoryMorphism)

- ▷ `GeneralizedMorphismByCospanWithSourceAid(alpha, beta)` (operation)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, c)$   
 The arguments are morphisms  $\alpha : a \leftarrow b$ , and  $\beta : b \rightarrow c$  in  $\mathbf{A}$ . The output is a generalized morphism by cospan defined by the composition the given two arrows regarded as generalized morphisms.

### 2.5.4 AsGeneralizedMorphismByCospan (for IsCapCategoryMorphism)

- ▷ `AsGeneralizedMorphismByCospan(alpha)` (attribute)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, b)$

The argument is a morphism  $\alpha : a \rightarrow b$  in  $\mathbf{A}$ . The output is the honest generalized morphism by cospan defined by  $\alpha$ .

### 2.5.5 GeneralizedMorphismCategoryByCospans (for IsCapCategory)

▷ `GeneralizedMorphismCategoryByCospans(A)` (attribute)

**Returns:** a category

The argument is an abelian category  $\mathbf{A}$ . The output is its generalized morphism category  $\mathbf{G}(\mathbf{A})$  by cospans.

### 2.5.6 GeneralizedMorphismByCospansObject (for IsCapCategoryObject)

▷ `GeneralizedMorphismByCospansObject(a)` (attribute)

**Returns:** an object in  $\mathbf{G}(\mathbf{A})$

The argument is an object  $a$  in an abelian category  $\mathbf{A}$ . The output is the object in the generalized morphism category by cospans whose underlying honest object is  $a$ .

## 2.6 Constructors of lifts of exact functors and natural (iso)morphisms

### 2.6.1 AsGeneralizedMorphismByCospan (for IsCapFunctor, IsString)

▷ `AsGeneralizedMorphismByCospan(F, name)` (operation)

Lift the *exact* functor  $F$  to a functor  $A \rightarrow B$ , where  $A := \text{GeneralizedMorphismCategoryByCospans}(\text{AsCapCategory}(\text{Source}(F)))$  and  $B := \text{GeneralizedMorphismCategoryByCospans}(\text{AsCapCategory}(\text{Range}(F)))$ .

## Chapter 3

# Generalized Morphism Category by Spans

### 3.1 GAP Categories

#### 3.1.1 `IsGeneralizedMorphismCategoryBySpansObject` (for `IsGeneralizedMorphismCategoryObject`)

▷ `IsGeneralizedMorphismCategoryBySpansObject(object)` (filter)

**Returns:** true or false

The GAP category of objects in the generalized morphism category by spans.

#### 3.1.2 `IsGeneralizedMorphismBySpan` (for `IsGeneralizedMorphism`)

▷ `IsGeneralizedMorphismBySpan(object)` (filter)

**Returns:** true or false

The GAP category of morphisms in the generalized morphism category by spans.

### 3.2 Properties

#### 3.2.1 `HasIdentityAsReversedArrow` (for `IsGeneralizedMorphismBySpan`)

▷ `HasIdentityAsReversedArrow(alpha)` (property)

**Returns:** true or false

The argument is a generalized morphism  $\alpha$  by a span  $a \leftarrow b \rightarrow c$ . The output is true if  $a \leftarrow b$  is congruent to an identity morphism, false otherwise.

### 3.3 Attributes

#### 3.3.1 `UnderlyingHonestObject` (for `IsGeneralizedMorphismCategoryBySpansObject`)

▷ `UnderlyingHonestObject(a)` (attribute)

**Returns:** an object in  $\mathbf{A}$

The argument is an object  $a$  in the generalized morphism category by spans. The output is its underlying honest object.

### 3.3.2 Arrow (for IsGeneralizedMorphismBySpan)

- ▷ `Arrow(alpha)` (attribute)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{A}}(b, c)$   
 The argument is a generalized morphism  $\alpha$  by a span  $a \leftarrow b \rightarrow c$ . The output is its arrow  $b \rightarrow c$ .

### 3.3.3 ReversedArrow (for IsGeneralizedMorphismBySpan)

- ▷ `ReversedArrow(alpha)` (attribute)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{A}}(b, a)$   
 The argument is a generalized morphism  $\alpha$  by a span  $a \leftarrow b \rightarrow c$ . The output is its reversed arrow  $a \leftarrow b$ .

### 3.3.4 NormalizedSpanTuple (for IsGeneralizedMorphismBySpan)

- ▷ `NormalizedSpanTuple(alpha)` (attribute)  
**Returns:** a pair of morphisms in  $\mathbf{A}$ .  
 The argument is a generalized morphism  $\alpha : a \rightarrow b$  by a span. The output is its normalized span pair  $(a \leftarrow d, d \rightarrow b)$ .

### 3.3.5 PseudoInverse (for IsGeneralizedMorphismBySpan)

- ▷ `PseudoInverse(alpha)` (attribute)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, a)$   
 The argument is a generalized morphism  $\alpha : a \rightarrow b$  by a span. The output is its pseudo inverse  $b \rightarrow a$ .

### 3.3.6 GeneralizedInverseBySpan (for IsCapCategoryMorphism)

- ▷ `GeneralizedInverseBySpan(alpha)` (attribute)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, a)$   
 The argument is a morphism  $\alpha : a \rightarrow b \in \mathbf{A}$ . The output is its generalized inverse  $b \rightarrow a$  by span.

### 3.3.7 IdempotentDefinedBySubobjectBySpan (for IsCapCategoryMorphism)

- ▷ `IdempotentDefinedBySubobjectBySpan(alpha)` (attribute)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, b)$   
 The argument is a subobject  $\alpha : a \hookrightarrow b \in \mathbf{A}$ . The output is the idempotent  $b \rightarrow b \in \mathbf{G}(\mathbf{A})$  by span defined by  $\alpha$ .

### 3.3.8 IdempotentDefinedByFactorobjectBySpan (for IsCapCategoryMorphism)

- ▷ `IdempotentDefinedByFactorobjectBySpan(alpha)` (attribute)  
**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, b)$   
 The argument is a factorobject  $\alpha : b \twoheadrightarrow a \in \mathbf{A}$ . The output is the idempotent  $b \rightarrow b \in \mathbf{G}(\mathbf{A})$  by span defined by  $\alpha$ .

### 3.3.9 NormalizedSpan (for IsGeneralizedMorphismBySpan)

▷ NormalizedSpan(*alpha*) (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, b)$

The argument is a generalized morphism  $\alpha : a \rightarrow b$  by a span. The output is its normalization by span.

## 3.4 Operations

### 3.4.1 GeneralizedMorphismFromFactorToSubobjectBySpan (for IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ GeneralizedMorphismFromFactorToSubobjectBySpan(*beta*, *alpha*) (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(c, a)$

The arguments are a factorobject  $\beta : b \rightarrow c$ , and a subobject  $\alpha : a \hookrightarrow b$ . The output is the generalized morphism by span from the factorobject to the subobject.

## 3.5 Constructors

### 3.5.1 GeneralizedMorphismBySpan (for IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ GeneralizedMorphismBySpan(*alpha*, *beta*) (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, b)$

The arguments are morphisms  $\alpha : a \leftarrow c$  and  $\beta : c \rightarrow b$  in  $\mathbf{A}$ . The output is a generalized morphism by span with arrow  $\beta$  and reversed arrow  $\alpha$ .

### 3.5.2 GeneralizedMorphismBySpan (for IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ GeneralizedMorphismBySpan(*alpha*, *beta*, *gamma*) (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, d)$

The arguments are morphisms  $\alpha : a \leftarrow b$ ,  $\beta : b \rightarrow c$ , and  $\gamma : c \leftarrow d$  in  $\mathbf{A}$ . The output is a generalized morphism by span defined by the composition the given three arrows regarded as generalized morphisms.

### 3.5.3 GeneralizedMorphismBySpanWithRangeAid (for IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ GeneralizedMorphismBySpanWithRangeAid(*alpha*, *beta*) (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, c)$

The arguments are morphisms  $\alpha : a \rightarrow b$ , and  $\beta : b \leftarrow c$  in  $\mathbf{A}$ . The output is a generalized morphism by span defined by the composition the given two arrows regarded as generalized morphisms.

### 3.5.4 AsGeneralizedMorphismBySpan (for IsCapCategoryMorphism)

▷ AsGeneralizedMorphismBySpan(*alpha*) (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, b)$

The argument is a morphism  $\alpha : a \rightarrow b$  in  $\mathbf{A}$ . The output is the honest generalized morphism by span defined by  $\alpha$ .

### 3.5.5 GeneralizedMorphismCategoryBySpans (for IsCapCategory)

▷ `GeneralizedMorphismCategoryBySpans(A)` (attribute)

**Returns:** a category

The argument is an abelian category  $\mathbf{A}$ . The output is its generalized morphism category  $\mathbf{G}(\mathbf{A})$  by spans.

### 3.5.6 GeneralizedMorphismBySpansObject (for IsCapCategoryObject)

▷ `GeneralizedMorphismBySpansObject(a)` (attribute)

**Returns:** an object in  $\mathbf{G}(\mathbf{A})$

The argument is an object  $a$  in an abelian category  $\mathbf{A}$ . The output is the object in the generalized morphism category by spans whose underlying honest object is  $a$ .



## Chapter 4

# Generalized Morphism Category by Three Arrows

### 4.1 GAP Categories

#### 4.1.1 `IsGeneralizedMorphismCategoryByThreeArrowsObject` (for `IsGeneralizedMorphismCategoryObject`)

▷ `IsGeneralizedMorphismCategoryByThreeArrowsObject(object)` (filter)

**Returns:** true or false

The GAP category of objects in the generalized morphism category by three arrows.

#### 4.1.2 `IsGeneralizedMorphismByThreeArrows` (for `IsGeneralizedMorphism`)

▷ `IsGeneralizedMorphismByThreeArrows(object)` (filter)

**Returns:** true or false

The GAP category of morphisms in the generalized morphism category by three arrows.

### 4.2 Properties

#### 4.2.1 `HasIdentitiesAsReversedArrows` (for `IsGeneralizedMorphismByThreeArrows`)

▷ `HasIdentitiesAsReversedArrows(alpha)` (property)

**Returns:** true or false

The argument is a generalized morphism  $\alpha$  by three arrows  $a \leftarrow b \rightarrow c \leftarrow d$ . The output is true if  $a \leftarrow b$  and  $c \leftarrow d$  are congruent to identity morphisms, false otherwise.

#### 4.2.2 `HasIdentityAsSourceAid` (for `IsGeneralizedMorphismByThreeArrows`)

▷ `HasIdentityAsSourceAid(alpha)` (property)

**Returns:** true or false

The argument is a generalized morphism  $\alpha$  by three arrows  $a \leftarrow b \rightarrow c \leftarrow d$ . The output is true if  $a \leftarrow b$  is congruent to an identity morphism, false otherwise.

### 4.2.3 HasIdentityAsRangeAid (for IsGeneralizedMorphismByThreeArrows)

▷ HasIdentityAsRangeAid( $\alpha$ ) (property)

**Returns:** true or false

The argument is a generalized morphism  $\alpha$  by three arrows  $a \leftarrow b \rightarrow c \leftarrow d$ . The output is true if  $c \leftarrow d$  is congruent to an identity morphism, false otherwise.

## 4.3 Attributes

### 4.3.1 UnderlyingHonestObject (for IsGeneralizedMorphismCategoryByThreeArrowsObject)

▷ UnderlyingHonestObject( $a$ ) (attribute)

**Returns:** an object in  $\mathbf{A}$

The argument is an object  $a$  in the generalized morphism category by three arrows. The output is its underlying honest object.

### 4.3.2 SourceAid (for IsGeneralizedMorphismByThreeArrows)

▷ SourceAid( $\alpha$ ) (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{A}}(b, a)$

The argument is a generalized morphism  $\alpha$  by three arrows  $a \leftarrow b \rightarrow c \leftarrow d$ . The output is its source aid  $a \leftarrow b$ .

### 4.3.3 RangeAid (for IsGeneralizedMorphismByThreeArrows)

▷ RangeAid( $\alpha$ ) (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{A}}(d, c)$

The argument is a generalized morphism  $\alpha$  by three arrows  $a \leftarrow b \rightarrow c \leftarrow d$ . The output is its range aid  $c \leftarrow d$ .

### 4.3.4 Arrow (for IsGeneralizedMorphismByThreeArrows)

▷ Arrow( $\alpha$ ) (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{A}}(b, c)$

The argument is a generalized morphism  $\alpha$  by three arrows  $a \leftarrow b \rightarrow c \leftarrow d$ . The output is its range aid  $b \rightarrow c$ .

### 4.3.5 PseudoInverse (for IsGeneralizedMorphismByThreeArrows)

▷ PseudoInverse( $\alpha$ ) (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, a)$

The argument is a generalized morphism  $\alpha : a \rightarrow b$  by three arrows. The output is its pseudo inverse  $b \rightarrow a$ .

### 4.3.6 GeneralizedInverseByThreeArrows (for IsCapCategoryMorphism)

▷ `GeneralizedInverseByThreeArrows(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, a)$

The argument is a morphism  $\alpha : a \rightarrow b \in \mathbf{A}$ . The output is its generalized inverse  $b \rightarrow a$  by three arrows.

### 4.3.7 IdempotentDefinedBySubobjectByThreeArrows (for IsCapCategoryMorphism)

▷ `IdempotentDefinedBySubobjectByThreeArrows(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, b)$

The argument is a subobject  $\alpha : a \hookrightarrow b \in \mathbf{A}$ . The output is the idempotent  $b \rightarrow b \in \mathbf{G}(\mathbf{A})$  by three arrows defined by  $\alpha$ .

### 4.3.8 IdempotentDefinedByFactorobjectByThreeArrows (for IsCapCategoryMorphism)

▷ `IdempotentDefinedByFactorobjectByThreeArrows(alpha)` (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, b)$

The argument is a factorobject  $\alpha : b \twoheadrightarrow a \in \mathbf{A}$ . The output is the idempotent  $b \rightarrow b \in \mathbf{G}(\mathbf{A})$  by three arrows defined by  $\alpha$ .

## 4.4 Operations

### 4.4.1 GeneralizedMorphismFromFactorToSubobjectByThreeArrows (for IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `GeneralizedMorphismFromFactorToSubobjectByThreeArrows(beta, alpha)` (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(c, a)$

The arguments are a factorobject  $\beta : b \twoheadrightarrow c$ , and a subobject  $\alpha : a \hookrightarrow b$ . The output is the generalized morphism by three arrows from the factorobject to the subobject.

### 4.4.2 CommonCostriction (for IsList)

▷ `CommonCostriction(L)` (operation)

**Returns:** a list of generalized morphisms

The argument is a list  $L$  of generalized morphisms by three arrows having the same range. The output is a list of generalized morphisms by three arrows which is the common costriction of  $L$ .

## 4.5 Constructors

### 4.5.1 GeneralizedMorphismByThreeArrows (for IsCapCategoryMorphism, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `GeneralizedMorphismByThreeArrows(alpha, beta, gamma)` (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, d)$

The arguments are morphisms  $\alpha : a \leftarrow b$ ,  $\beta : b \rightarrow c$ , and  $\gamma : c \leftarrow d$  in  $\mathbf{A}$ . The output is a generalized morphism by three arrows with source aid  $\alpha$ , arrow  $\beta$ , and range aid  $\gamma$ .

#### 4.5.2 GeneralizedMorphismByThreeArrowsWithSourceAid (for IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ GeneralizedMorphismByThreeArrowsWithSourceAid(*alpha*, *beta*) (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, c)$

The arguments are morphisms  $\alpha : a \leftarrow b$ , and  $\beta : b \rightarrow c$  in  $\mathbf{A}$ . The output is a generalized morphism by three arrows defined by the composition the given two arrows regarded as generalized morphisms.

#### 4.5.3 GeneralizedMorphismByThreeArrowsWithRangeAid (for IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ GeneralizedMorphismByThreeArrowsWithRangeAid(*beta*, *gamma*) (operation)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(b, d)$

The arguments are morphisms  $\beta : b \rightarrow c$ , and  $\gamma : c \leftarrow d$  in  $\mathbf{A}$ . The output is a generalized morphism by three arrows defined by the composition the given two arrows regarded as generalized morphisms.

#### 4.5.4 AsGeneralizedMorphismByThreeArrows (for IsCapCategoryMorphism)

▷ AsGeneralizedMorphismByThreeArrows(*alpha*) (attribute)

**Returns:** a morphism in  $\text{Hom}_{\mathbf{G}(\mathbf{A})}(a, b)$

The argument is a morphism  $\alpha : a \rightarrow b$  in  $\mathbf{A}$ . The output is the honest generalized morphism by three arrows defined by  $\alpha$ .

#### 4.5.5 GeneralizedMorphismCategoryByThreeArrows (for IsCapCategory)

▷ GeneralizedMorphismCategoryByThreeArrows(*A*) (attribute)

**Returns:** a category

The argument is an abelian category  $\mathbf{A}$ . The output is its generalized morphism category  $\mathbf{G}(\mathbf{A})$  by three arrows.

#### 4.5.6 GeneralizedMorphismByThreeArrowsObject (for IsCapCategoryObject)

▷ GeneralizedMorphismByThreeArrowsObject(*a*) (attribute)

**Returns:** an object in  $\mathbf{G}(\mathbf{A})$

The argument is an object  $a$  in an abelian category  $\mathbf{A}$ . The output is the object in the generalized morphism category by three arrows whose underlying honest object is  $a$ .

## Chapter 5

# Conversion functors for generalized morphisms

### 5.1 Functors from Cospans

#### 5.1.1 FunctorFromCospansToThreeArrows (for IsCapCategory)

▷ `FunctorFromCospansToThreeArrows(C)` (attribute)

**Returns:** a functor

For the given category  $C$ , this attribute is the functor from the cospan generalized morphism category of  $C$  to the generalized morphism category modeled by three arrows.

#### 5.1.2 FunctorFromCospansToSpans (for IsCapCategory)

▷ `FunctorFromCospansToSpans(C)` (attribute)

**Returns:** a functor

For the given category  $C$ , this attribute is the functor from the cospan generalized morphism category of  $C$  to the generalized morphism category modeled by spans.

### 5.2 Functors from Spans

#### 5.2.1 FunctorFromSpansToThreeArrows (for IsCapCategory)

▷ `FunctorFromSpansToThreeArrows(C)` (attribute)

**Returns:** a functor

For the given category  $C$ , this attribute is the functor from the span generalized morphism category of  $C$  to the generalized morphism category modeled by three arrows.

#### 5.2.2 FunctorFromSpansToCospans (for IsCapCategory)

▷ `FunctorFromSpansToCospans(C)` (attribute)

**Returns:** a functor

For the given category  $C$ , this attribute is the functor from the span generalized morphism category of  $C$  to the generalized morphism category modeled by cospans.

## 5.3 Functors from Three Arrows

### 5.3.1 FunctorFromThreeArrowsToCospans (for IsCapCategory)

▷ `FunctorFromThreeArrowsToCospans(C)` (attribute)

**Returns:** a functor

For the given category  $C$ , this attribute is the functor from the three arrow generalized morphism category of  $C$  to the generalized morphism category modeled by cospans.

### 5.3.2 FunctorFromThreeArrowsToSpans (for IsCapCategory)

▷ `FunctorFromThreeArrowsToSpans(C)` (attribute)

**Returns:** a functor

For the given category  $C$ , this attribute is the functor from the three arrow generalized morphism category of  $C$  to the generalized morphism category modeled by spans.

## Chapter 6

# Serre Quotients Subcategory

This is an implementation of a convenience object for Serre quotients. The Subcategory implemented in this file is not a CAP category at all, but only a handler for the Serre quotient construction. It does not contain objects or anything useful, it is just a wrapper for the function the Serre quotient is based upon.

### 6.1 implementation

#### 6.1.1 FullSubcategoryByMembershipFunction (for IsCapCategory, IsFunction)

▷ FullSubcategoryByMembershipFunction(*C*, *func*) (operation)

**Returns:** a function handler

Creates an object which handles the function to create a Serre quotient category. It can be used instead of the function for Serre quotients. Note that the result is *\*NOT A CATEGORY\** and can not be seen as one.

## Chapter 7

# Serre Quotients

Serre quotients are implemented using generalized morphisms. A Serre quotient category is the quotient of an abelian category  $A$  by a thick subcategory  $C$ . The objects of the quotient are the objects from  $A$ , the morphisms are a limit construction. In the implementation those morphisms are modeled by generalized morphisms, and therefore there are, like in the generalized morphism case, three types of Serre quotients.

### 7.1 General operations

As in the generalized morphism case, the generic constructors depend on the generalized morphism standard. Please note that for implementations the specialized constructors should be used.

#### 7.1.1 `IsSerreQuotientCategoryObject` (for `IsCapCategoryObject`)

▷ `IsSerreQuotientCategoryObject(arg)` (filter)

**Returns:** true or false

The category of objects in the category of Serre quotients. For actual objects this needs to be specialized.

#### 7.1.2 `IsSerreQuotientCategoryMorphism` (for `IsCapCategoryMorphism`)

▷ `IsSerreQuotientCategoryMorphism(arg)` (filter)

**Returns:** true or false

The category of morphisms in the category of Serre quotients. For actual morphisms this needs to be specialized.

#### 7.1.3 `SerreQuotientCategory` (for `IsCapCategory`, `IsFunction`, `IsString`)

▷ `SerreQuotientCategory(A, func[, name])` (operation)

**Returns:** a CAP category

Creates a Serre quotient category  $S$  with name  $name$  out of an Abelian category  $A$ . If  $name$  is not given, a generic name is constructed out of the name of  $A$ . The argument  $func$  must be a unary function on the objects of  $A$  deciding the membership in the thick subcategory  $C$  mentioned above.



### 7.1.4 AsSerreQuotientCategoryObject (for IsCapCategory, IsCapCategoryObject)

▷ `AsSerreQuotientCategoryObject(A/C, M)` (operation)

**Returns:** an object

Given a Serre quotient category  $A/C$  and an object  $M$  in  $A$ , this constructor returns the corresponding object in the Serre quotient category.

### 7.1.5 SerreQuotientCategoryMorphism (for IsCapCategory, IsGeneralizedMorphism)

▷ `SerreQuotientCategoryMorphism(A/C, phi)` (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  and a generalized morphism  $phi$  in the generalized morphism category  $A/C$  is modeled upon, this constructor returns the corresponding morphism in the Serre quotient category.

### 7.1.6 SerreQuotientCategoryMorphism (for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `SerreQuotientCategoryMorphism(A/C, iota, phi, pi)` (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  and three morphisms  $\iota : M' \rightarrow M$ ,  $\phi : M' \rightarrow N'$  and  $\pi : N \rightarrow N'$  this operation constructs a morphism in the Serre quotient category.

### 7.1.7 SerreQuotientCategoryMorphism (for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `SerreQuotientCategoryMorphism(A/C, alpha, beta)` (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  and two morphisms of the form  $\alpha : X \rightarrow M$  and  $\beta : X \rightarrow N$  or  $\alpha : M \rightarrow X$  and  $\beta : N \rightarrow X$ , this operation constructs the corresponding morphism in the Serre quotient category. This operation is only implemented if  $A/C$  is modeled upon a span generalized morphism category in the first option or upon a cospan category in the second.

### 7.1.8 SerreQuotientCategoryMorphismWithSourceAid (for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `SerreQuotientCategoryMorphismWithSourceAid(A/C, alpha, beta)` (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  and two morphisms  $\alpha : M \rightarrow X$  and  $\beta : X \rightarrow N$  this operation constructs the corresponding morphism in the Serre quotient category.

### 7.1.9 SerreQuotientCategoryMorphismWithRangeAid (for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `SerreQuotientCategoryMorphismWithRangeAid(A/C, alpha, beta)` (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  and two morphisms  $\alpha : X \rightarrow M$  and  $\beta : X \rightarrow N$  this operation constructs the corresponding morphism in the Serre quotient category.

### 7.1.10 AsSerreQuotientCategoryMorphism (for IsCapCategory, IsCapCategoryMorphism)

▷ `AsSerreQuotientCategoryMorphism( $A/C$ ,  $phi$ )` (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  and a morphism  $phi$  in  $A$ , this constructor returns the corresponding morphism in the Serre quotient category.

### 7.1.11 SubcategoryMembershipTestFunctionForSerreQuotient (for IsCapCategory)

▷ `SubcategoryMembershipTestFunctionForSerreQuotient( $C$ )` (attribute)

**Returns:** a function

When a Serre quotient category is created, a membership function for the subcategory is given. This attribute stores and returns this function

### 7.1.12 UnderlyingHonestCategory (for IsCapCategory)

▷ `UnderlyingHonestCategory( $A/C$ )` (attribute)

**Returns:** a category

For a Serre quotient category  $A/C$  this attribute returns the category  $A$ .

### 7.1.13 UnderlyingGeneralizedMorphismCategory (for IsCapCategory)

▷ `UnderlyingGeneralizedMorphismCategory( $A/C$ )` (attribute)

**Returns:** a category

For a Serre quotient category  $A/C$  this attribute returns generalized morphism category the quotient is modelled upon.

### 7.1.14 UnderlyingGeneralizedObject (for IsSerreQuotientCategoryObject)

▷ `UnderlyingGeneralizedObject( $M$ )` (attribute)

**Returns:** an object

For an object  $M$  in the Serre quotient category  $A/C$  this attribute returns the corresponding object in the generalized morphism category the quotient is modelled upon.

### 7.1.15 UnderlyingHonestObject (for IsSerreQuotientCategoryObject)

▷ `UnderlyingHonestObject( $M$ )` (attribute)

**Returns:** an object

For an object  $M$  in the Serre quotient category  $A/C$  this attribute returns the corresponding object in  $A$ .

### 7.1.16 UnderlyingGeneralizedMorphism (for IsSerreQuotientCategoryMorphism)

▷ UnderlyingGeneralizedMorphism(*phi*) (attribute)

**Returns:** a morphism

For a morphism *phi* in the Serre quotient category  $A/C$  this attribute returns the corresponding generalized morphism in the generalized morphism category the quotient is modelled upon.

### 7.1.17 CanonicalProjection (for IsCapCategory)

▷ CanonicalProjection( $A/C$ ) (attribute)

**Returns:** a functor

Given a Serre quotient category  $A/C$ , this operation returns the canonical projection functor  $A \rightarrow A/C$ .

## 7.2 Serre quotients by cospans

### 7.2.1 SerreQuotientCategoryByCospans (for IsCapCategory, IsFunction, IsString)

▷ SerreQuotientCategoryByCospans( $A$ , *func* [, *name*]) (operation)

**Returns:** a CAP category

Creates a Serre quotient category  $S$  with name *name* out of an Abelian category  $A$ . The Serre quotient category will be modeled upon the generalized morphisms by cospans category of  $A$ . If *name* is not given, a generic name is constructed out of the name of  $A$ . The argument *func* must be a unary function on the objects of  $A$  deciding the membership in the thick subcategory  $C$  mentioned above.

### 7.2.2 AsSerreQuotientCategoryByCospansObject (for IsCapCategory, IsCapCategoryObject)

▷ AsSerreQuotientCategoryByCospansObject( $A/C$ ,  $M$ ) (operation)

**Returns:** an object

Given a Serre quotient category  $A/C$  modeled by cospans and an object  $M$  in  $A$ , this constructor returns the corresponding object in the Serre quotient category.

### 7.2.3 SerreQuotientCategoryByCospansMorphism (for IsCapCategory, IsGeneralizedMorphismByCospan)

▷ SerreQuotientCategoryByCospansMorphism( $A/C$ , *phi*) (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by cospans and a generalized morphism *phi* in the generalized morphism category  $A/C$  is modeled upon, this constructor returns the corresponding morphism in the Serre quotient category.

### 7.2.4 SerreQuotientCategoryByCospansMorphism (for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ SerreQuotientCategoryByCospansMorphism( $A/C$ , *iota*, *phi*, *pi*) (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by cospans and three morphisms  $\iota : M' \rightarrow M$ ,  $\phi : M' \rightarrow N'$  and  $\pi : N \rightarrow N'$  this operation constructs a morphism in the Serre quotient category.

### 7.2.5 SerreQuotientCategoryByCospansMorphismWithSourceAid (for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ SerreQuotientCategoryByCospansMorphismWithSourceAid( $A/C$ ,  $\alpha$ ,  $\beta$ ) (operation)  
**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by cospans and two morphisms  $\alpha : M \rightarrow X$  and  $\beta : X \rightarrow N$  this operation constructs the corresponding morphism in the Serre quotient category.

### 7.2.6 SerreQuotientCategoryByCospansMorphism (for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ SerreQuotientCategoryByCospansMorphism( $A/C$ ,  $\alpha$ ,  $\beta$ ) (operation)  
**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by cospans and two morphisms  $\alpha : X \rightarrow M$  and  $\beta : X \rightarrow N$  this operation constructs the corresponding morphism in the Serre quotient category.

### 7.2.7 AsSerreQuotientCategoryByCospansMorphism (for IsCapCategory, IsCapCategoryMorphism)

▷ AsSerreQuotientCategoryByCospansMorphism( $A/C$ ,  $\phi$ ) (operation)  
**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by cospans and a morphism  $\phi$  in  $A$ , this constructor returns the corresponding morphism in the Serre quotient category.

## 7.3 Serre Quotients by Spans

### 7.3.1 SerreQuotientCategoryBySpans (for IsCapCategory, IsFunction, IsString)

▷ SerreQuotientCategoryBySpans( $A$ ,  $func$  [,  $name$ ]) (operation)  
**Returns:** a CAP category

Creates a Serre quotient category  $S$  with name  $name$  out of an Abelian category  $A$ . The Serre quotient category will be modeled upon the generalized morphisms by spans category of  $A$ . If  $name$  is not given, a generic name is constructed out of the name of  $A$ . The argument  $func$  must be a unary function on the objects of  $A$  deciding the membership in the thick subcategory  $C$  mentioned above.

### 7.3.2 AsSerreQuotientCategoryBySpansObject (for IsCapCategory, IsCapCategoryObject)

▷ AsSerreQuotientCategoryBySpansObject( $A/C$ ,  $M$ ) (operation)  
**Returns:** an object

Given a Serre quotient category  $A/C$  modeled by spans and an object  $M$  in  $A$ , this constructor returns the corresponding object in the Serre quotient category.

### 7.3.3 SerreQuotientCategoryBySpansMorphism (for IsCapCategory, IsGeneralizedMorphismBySpan)

▷ SerreQuotientCategoryBySpansMorphism( $A/C$ ,  $phi$ ) (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by spans and a generalized morphism  $phi$  in the generalized morphism category  $A/C$  is modeled upon, this constructor returns the corresponding morphism in the Serre quotient category.

### 7.3.4 SerreQuotientCategoryBySpansMorphism (for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ SerreQuotientCategoryBySpansMorphism( $A/C$ ,  $iota$ ,  $phi$ ,  $pi$ ) (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by spans and three morphisms  $\iota : M' \rightarrow M$ ,  $\phi : M' \rightarrow N'$  and  $\pi : N \rightarrow N'$  this operation constructs a morphism in the Serre quotient category.

### 7.3.5 SerreQuotientCategoryBySpansMorphism (for IsCapCategory, IsCapCategoryMorphism)

▷ SerreQuotientCategoryBySpansMorphism( $A/C$ ,  $alpha$ ,  $beta$ ) (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by spans and two morphisms  $\alpha : M \rightarrow X$  and  $\beta : X \rightarrow N$  this operation constructs the corresponding morphism in the Serre quotient category.

### 7.3.6 SerreQuotientCategoryBySpansMorphismWithRangeAid (for IsCapCategory, IsCapCategoryMorphism)

▷ SerreQuotientCategoryBySpansMorphismWithRangeAid( $A/C$ ,  $alpha$ ,  $beta$ ) (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by spans and two morphisms  $\alpha : X \rightarrow M$  and  $\beta : X \rightarrow N$  this operation constructs the corresponding morphism in the Serre quotient category.

### 7.3.7 AsSerreQuotientCategoryBySpansMorphism (for IsCapCategory, IsCapCategoryMorphism)

▷ AsSerreQuotientCategoryBySpansMorphism( $A/C$ ,  $phi$ ) (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by spans and a morphism  $phi$  in  $A$ , this constructor returns the corresponding morphism in the Serre quotient category.

## 7.4 Serre Quotients modeled by three arrows

### 7.4.1 SerreQuotientCategoryByThreeArrows (for IsCapCategory, IsFunction, IsString)

▷ SerreQuotientCategoryByThreeArrows( $A$ ,  $func$  [,  $name$ ]) (operation)

**Returns:** a CAP category

Creates a Serre quotient category  $S$  with name *name* out of an Abelian category  $A$ . The Serre quotient category will be modeled upon the generalized morphisms by three arrows category of  $A$ . If *name* is not given, a generic name is constructed out of the name of  $A$ . The argument *func* must be a unary function on the objects of  $A$  deciding the membership in the thick subcategory  $C$  mentioned above.

#### 7.4.2 AsSerreQuotientCategoryByThreeArrowsObject (for IsCapCategory, IsCapCategoryObject)

▷ `AsSerreQuotientCategoryByThreeArrowsObject( $A/C$ ,  $M$ )` (operation)

**Returns:** an object

Given a Serre quotient category  $A/C$  modeled by three arrows and an object  $M$  in  $A$ , this constructor returns the corresponding object in the Serre quotient category.

#### 7.4.3 SerreQuotientCategoryByThreeArrowsMorphism (for IsCapCategory, IsGeneralizedMorphismByThreeArrows)

▷ `SerreQuotientCategoryByThreeArrowsMorphism( $A/C$ ,  $phi$ )` (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by three arrows and a generalized morphism  $phi$  in the generalized morphism category  $A/C$  is modeled upon, this constructor returns the corresponding morphism in the Serre quotient category.

#### 7.4.4 SerreQuotientCategoryByThreeArrowsMorphism (for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `SerreQuotientCategoryByThreeArrowsMorphism( $A/C$ ,  $iota$ ,  $phi$ ,  $pi$ )` (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by three arrows and three morphisms  $\iota : M' \rightarrow M$ ,  $\phi : M' \rightarrow N'$  and  $\pi : N \rightarrow N'$  this operation constructs a morphism in the Serre quotient category.

#### 7.4.5 SerreQuotientCategoryByThreeArrowsMorphismWithSourceAid (for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `SerreQuotientCategoryByThreeArrowsMorphismWithSourceAid( $A/C$ ,  $alpha$ ,  $beta$ )` (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by three arrows and two morphisms  $\alpha : M \rightarrow X$  and  $\beta : X \rightarrow N$  this operation constructs the corresponding morphism in the Serre quotient category.

#### 7.4.6 SerreQuotientCategoryByThreeArrowsMorphismWithRangeAid (for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism)

▷ `SerreQuotientCategoryByThreeArrowsMorphismWithRangeAid( $A/C$ ,  $alpha$ ,  $beta$ )` (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by three arrows and two morphisms  $\alpha : X \rightarrow M$  and  $\beta : X \rightarrow N$  this operation constructs the corresponding morphism in the Serre quotient category.

#### 7.4.7 AsSerreQuotientCategoryByThreeArrowsMorphism (for IsCapCategory, Is-CapCategoryMorphism)

▷ AsSerreQuotientCategoryByThreeArrowsMorphism( $A/C$ ,  $phi$ ) (operation)

**Returns:** a morphism

Given a Serre quotient category  $A/C$  modeled by three arrows and a morphism  $phi$  in  $A$ , this constructor returns the corresponding morphism in the Serre quotient category.

## Chapter 8

# Serre Quotients Functors

The operations in this chapter construct conversion functors between two Serre quotients of different standards. Please note that all the operations DO NOT CARE if the Serre quotients are modeling the same category, they only care whether the categories are based upon the same underlying honest category.

### 8.1 Functors

#### 8.1.1 SerreQuotientConversionFunctor (for IsCapCategory, IsCapCategory)

▷ SerreQuotientConversionFunctor( $A$ ,  $B$ ) (operation)

**Returns:** a functor

Given two Serre quotients  $A$  and  $B$  of the same category  $C$  by equivalent functors, this operation returns the conversion functor between the two categories. Please note that this function does not check the quotients in any sense, i.e., whether the functors are equivalent.



## Chapter 9

# Examples and Tests

### 9.1 Basic Commands

Example

```
gap> Q := HomalgFieldOfRationals();
gap> A := VectorSpaceObject( 4, Q );
gap> B := VectorSpaceObject( 3, Q );
gap> C := VectorSpaceObject( 2, Q );
gap> alpha := VectorSpaceMorphism( A,
> HomalgMatrix( [ [ 1, 1, 1 ], [ 0, 1, 1 ],
> [ 1, 0, 1 ], [ 1, 1, 0 ] ], 4, 3, Q ), B );
gap> gamma := VectorSpaceMorphism( C,
> HomalgMatrix( [ [ -1, 1, -1 ], [ 1, 0, -1 ] ], 2, 3, Q ), B );
gap> p := ProjectionInFactorOfFiberProduct( [ alpha, gamma ], 1 );
gap> q := ProjectionInFactorOfFiberProduct( [ alpha, gamma ], 2 );
gap> PreCompose( AsGeneralizedMorphism( alpha ), GeneralizedInverse( gamma ) );
<A morphism in Generalized morphism category of Category of matrices over Q>
gap> gen1 := PreCompose( AsGeneralizedMorphism( alpha ),
> GeneralizedInverse( gamma ) );
<A morphism in Generalized morphism category of Category of matrices over Q>
gap> gen2 := PreCompose( GeneralizedInverse( p ), AsGeneralizedMorphism( q ) );
<A morphism in Generalized morphism category of Category of matrices over Q>
gap> IsCongruentForMorphisms( gen1, gen2 );
true
```

### 9.2 Intersection of Nodal Curve and Cusp

We are going to intersect the nodal curve  $f = y^2 - x^2(x + 1)$  and the cusp  $g = (x + y)^2 - (y - x)^3$ . The two curves are arranged in a way such that they intersect at  $(0, 0)$  with intersection number as high as possible. We are going to compute this intersection number using the definition of the intersection number as the length of the module  $R/(f, g)$  localized at  $(0, 0)$ . In order to model modules over the localization of  $Q[x, y]$  at  $(0, 0)$ , we use a suitable Serre quotient category. 1 2 1 1 true We are going to intersect the nodal curve  $f = y^2 - x^2(x + 1)$  and the cusp  $g = (x + y)^2 - (y - x)^3$ . The two curves are arranged in a way such that they intersect at  $(0, 0)$  with intersection number as high as possible. We are going to compute this intersection number using the definition of the intersection number as the length of the module  $R/(f, g)$  localized at  $(0, 0)$ . In order to model modules over the localization of  $Q[x, y]$  at  $(0, 0)$ , we use a suitable Serre quotient category. 1 2 1 1 true We are going to intersect

the nodal curve  $f = y^2 - x^2(x+1)$  and the cusp  $g = (x+y)^2 - (y-x)^3$ . The two curves are arranged in a way such that they intersect at  $(0,0)$  with intersection number as high as possible. We are going to compute this intersection number using the definition of the intersection number as the length of the module  $R/(f,g)$  localized at  $(0,0)$ . In order to model modules over the localization of  $Q[x,y]$  at  $(0,0)$ , we use a suitable Serre quotient category. 1 2 1 1 true

### 9.3 Sweep

Geometric interpretation of sweeping a matrix by Terence Tao.

Example

```
gap> Q := HomalgFieldOfRationals();;
gap> V := VectorSpaceObject( 3, Q );;
gap> mat := HomalgMatrix( [ [ 9, 8, 7 ], [ 6, 5, 4 ], [ 3, 2, 1 ] ], 3, 3, Q );;
gap> alpha := VectorSpaceMorphism( V, mat, V );;
gap> graph := FiberProductEmbeddingInDirectSum(
> [ alpha, IdentityMorphism( V ) ] );;
gap> Display( graph );
[ [ 1, -2, 1, 0, 0, 0 ],
  [ -4/3, 7/3, 0, 2, 1, 0 ],
  [ 5/3, -8/3, 0, -1, 0, 1 ] ]
```

A split monomorphism in Category of matrices over Q

```
gap> D := DirectSum( V, V );;
gap> rotmat := HomalgMatrix( [ [ 0, 0, 0, -1, 0, 0 ],
> [ 0, 1, 0, 0, 0, 0 ],
> [ 0, 0, 1, 0, 0, 0 ],
> [ 1, 0, 0, 0, 0, 0 ],
> [ 0, 0, 0, 0, 1, 0 ],
> [ 0, 0, 0, 0, 0, 1 ] ],
> 6, 6, Q );;
gap> rot := VectorSpaceMorphism( D, rotmat, D );;
gap> p := PreCompose( graph, rot );;
gap> Display( p );
[ [ 0, -2, 1, -1, 0, 0 ],
  [ 2, 7/3, 0, 4/3, 1, 0 ],
  [ -1, -8/3, 0, -5/3, 0, 1 ] ]
```

A morphism in Category of matrices over Q

```
gap> pi1 := ProjectionInFactorOfDirectSum( [ V, V ], 1 );;
gap> pi2 := ProjectionInFactorOfDirectSum( [ V, V ], 2 );;
gap> reversed_arrow := PreCompose( p, pi1 );;
gap> arrow := PreCompose( p, pi2 );;
gap> g := GeneralizedMorphismBySpan( reversed_arrow, arrow );;
gap> IsHonest( g );
true
gap> sweep_1_alpha := HonestRepresentative( g );;
gap> Display( sweep_1_alpha );
[ [ -1/9, 8/9, 7/9 ],
  [ 2/3, -1/3, -2/3 ],
  [ 1/3, -2/3, -4/3 ] ]
```

A morphism in Category of matrices over  $\mathbb{Q}$

```
gap> Display( alpha );
```

```
[ [ 9, 8, 7 ],  
  [ 6, 5, 4 ],  
  [ 3, 2, 1 ] ]
```

A morphism in Category of matrices over  $\mathbb{Q}$

# Index

- Arrow
  - for `IsGeneralizedMorphismByCospan`, 10
  - for `IsGeneralizedMorphismBySpan`, 14
  - for `IsGeneralizedMorphismByThreeArrows`, 18
- `AsGeneralizedMorphism`
  - for `IsCapCategoryMorphism`, 8
- `AsGeneralizedMorphismByCospan`
  - for `IsCapCategoryMorphism`, 11
  - for `IsCapFunctor`, `IsString`, 12
- `AsGeneralizedMorphismBySpan`
  - for `IsCapCategoryMorphism`, 15
- `AsGeneralizedMorphismByThreeArrows`
  - for `IsCapCategoryMorphism`, 20
- `AsSerreQuotientCategoryByCospansMorphism`
  - for `IsCapCategory`, `IsCapCategoryMorphism`, 28
- `AsSerreQuotientCategoryByCospansObject`
  - for `IsCapCategory`, `IsCapCategoryObject`, 27
- `AsSerreQuotientCategoryBySpansMorphism`
  - for `IsCapCategory`, `IsCapCategoryMorphism`, 29
- `AsSerreQuotientCategoryBySpansObject`
  - for `IsCapCategory`, `IsCapCategoryObject`, 28
- `AsSerreQuotientCategoryByThreeArrowsMorphism`
  - for `IsCapCategory`, `IsCapCategoryMorphism`, 31
- `AsSerreQuotientCategoryByThreeArrowsObject`
  - for `IsCapCategory`, `IsCapCategoryObject`, 30
- `AsSerreQuotientCategoryMorphism`
  - for `IsCapCategory`, `IsCapCategoryMorphism`, 26
- `AsSerreQuotientCategoryObject`
  - for `IsCapCategory`, `IsCapCategoryObject`, 25
- `AssociatedMorphism`
  - for `IsGeneralizedMorphism`, 5
- `CanonicalProjection`
  - for `IsCapCategory`, 27
- `Codomain`
  - for `IsGeneralizedMorphism`, 5
- `CommonCostriction`
  - for `IsList`, 19
- `CommonRestriction`
  - for `IsList`, 6
- `ConcatenationProduct`
  - for `IsList`, 6
- `DomainAssociatedMorphismCodomainTriple`
  - for `IsGeneralizedMorphism`, 5
- `DomainOfGeneralizedMorphism`
  - for `IsGeneralizedMorphism`, 4
- `FullSubcategoryByMembershipFunction`
  - for `IsCapCategory`, `IsFunction`, 23
- `FunctorFromCospansToSpans`
  - for `IsCapCategory`, 21
- `FunctorFromCospansToThreeArrows`
  - for `IsCapCategory`, 21
- `FunctorFromSpansToCospans`
  - for `IsCapCategory`, 21
- `FunctorFromSpansToThreeArrows`
  - for `IsCapCategory`, 21
- `FunctorFromThreeArrowsToCospans`
  - for `IsCapCategory`, 22
- `FunctorFromThreeArrowsToSpans`
  - for `IsCapCategory`, 22
- `GeneralizedInverse`
  - for `IsCapCategoryMorphism`, 5
- `GeneralizedInverseByCospan`
  - for `IsCapCategoryMorphism`, 10
- `GeneralizedInverseBySpan`
  - for `IsCapCategoryMorphism`, 14
- `GeneralizedInverseByThreeArrows`
  - for `IsCapCategoryMorphism`, 19
- `GeneralizedMorphism`

- for IsCapCategoryMorphism, IsCapCategoryMorphism, 8
- for IsCapCategoryMorphism, IsCapCategoryMorphism, IsCapCategoryMorphism, 8
- GeneralizedMorphismByCospan
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 11
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, IsCapCategoryMorphism, 11
- GeneralizedMorphismByCospansObject
  - for IsCapCategoryObject, 12
- GeneralizedMorphismByCospanWithSourceAid
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 11
- GeneralizedMorphismBySpan
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 15
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, IsCapCategoryMorphism, 15
- GeneralizedMorphismBySpansObject
  - for IsCapCategoryObject, 16
- GeneralizedMorphismBySpanWithRangeAid
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 15
- GeneralizedMorphismByThreeArrows
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, IsCapCategoryMorphism, 19
- GeneralizedMorphismByThreeArrowsObject
  - for IsCapCategoryObject, 20
- GeneralizedMorphismByThreeArrowsWithRangeAid
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 20
- GeneralizedMorphismByThreeArrowsWithSourceAid
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 20
- GeneralizedMorphismCategory
  - for IsCapCategory, 7
- GeneralizedMorphismCategoryByCospans
  - for IsCapCategory, 12
- GeneralizedMorphismCategoryBySpans
  - for IsCapCategory, 16
- GeneralizedMorphismCategoryByThreeArrows
  - for IsCapCategory, 20
- GeneralizedMorphismFromFactorToSubobject
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 6
- GeneralizedMorphismFromFactorToSubobjectByCospan
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 11
- GeneralizedMorphismFromFactorToSubobjectBySpan
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 15
- GeneralizedMorphismFromFactorToSubobjectByThreeArrows
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 19
- GeneralizedMorphismObject
  - for IsCapCategoryObject, 7
- GeneralizedMorphismWithRangeAid
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 8
- GeneralizedMorphismWithSourceAid
  - for IsCapCategoryMorphism, IsCapCategoryMorphism, 8
- HasFullCodomain
  - for IsGeneralizedMorphism, 7
- HasFullDomain
  - for IsGeneralizedMorphism, 6
- HasIdentitiesAsReversedArrows
  - for IsGeneralizedMorphismByThreeArrows, 17
- HasIdentityAsRangeAid
  - for IsGeneralizedMorphismByThreeArrows, 18
- HasIdentityAsReversedArrow
  - for IsGeneralizedMorphismByCospan, 9
  - for IsGeneralizedMorphismBySpan, 13
- HasIdentityAsSourceAid
  - for IsGeneralizedMorphismByThreeArrows, 17
- HonestRepresentative
  - for IsGeneralizedMorphism, 5

- IdempotentDefinedByFactorobject  
for IsCapCategoryMorphism, [5](#)
- IdempotentDefinedByFactorobjectBy-  
Cospan  
for IsCapCategoryMorphism, [10](#)
- IdempotentDefinedByFactorobjectBySpan  
for IsCapCategoryMorphism, [14](#)
- IdempotentDefinedByFactorobjectBy-  
ThreeArrows  
for IsCapCategoryMorphism, [19](#)
- IdempotentDefinedBySubobject  
for IsCapCategoryMorphism, [5](#)
- IdempotentDefinedBySubobjectByCospan  
for IsCapCategoryMorphism, [10](#)
- IdempotentDefinedBySubobjectBySpan  
for IsCapCategoryMorphism, [14](#)
- IdempotentDefinedBySubobjectByThree-  
Arrows  
for IsCapCategoryMorphism, [19](#)
- IsGeneralizedMorphism  
for IsCapCategoryMorphism, [4](#)
- IsGeneralizedMorphismByCospan  
for IsGeneralizedMorphism, [9](#)
- IsGeneralizedMorphismBySpan  
for IsGeneralizedMorphism, [13](#)
- IsGeneralizedMorphismByThreeArrows  
for IsGeneralizedMorphism, [17](#)
- IsGeneralizedMorphismCategoryBy-  
CospansObject  
for IsGeneralizedMorphismCategoryObject,  
[9](#)
- IsGeneralizedMorphismCategoryBySpans-  
Object  
for IsGeneralizedMorphismCategoryObject,  
[13](#)
- IsGeneralizedMorphismCategoryByThree-  
ArrowsObject  
for IsGeneralizedMorphismCategoryObject,  
[17](#)
- IsGeneralizedMorphismCategoryObject  
for IsCapCategoryObject, [4](#)
- IsHonest  
for IsGeneralizedMorphism, [6](#)
- IsSerreQuotientCategoryMorphism  
for IsCapCategoryMorphism, [24](#)
- IsSerreQuotientCategoryObject  
for IsCapCategoryObject, [24](#)
- IsSingleValued  
for IsGeneralizedMorphism, [7](#)
- IsTotal  
for IsGeneralizedMorphism, [7](#)
- NormalizedCospan  
for IsGeneralizedMorphismByCospan, [11](#)
- NormalizedCospanTuple  
for IsGeneralizedMorphismByCospan, [10](#)
- NormalizedSpan  
for IsGeneralizedMorphismBySpan, [15](#)
- NormalizedSpanTuple  
for IsGeneralizedMorphismBySpan, [14](#)
- PseudoInverse  
for IsGeneralizedMorphismByCospan, [10](#)  
for IsGeneralizedMorphismBySpan, [14](#)  
for IsGeneralizedMorphismByThreeArrows,  
[18](#)
- RangeAid  
for IsGeneralizedMorphismByThreeArrows,  
[18](#)
- ReversedArrow  
for IsGeneralizedMorphismByCospan, [10](#)  
for IsGeneralizedMorphismBySpan, [14](#)
- SerreQuotientCategory  
for IsCapCategory, IsFunction, IsString, [24](#)
- SerreQuotientCategoryByCospans  
for IsCapCategory, IsFunction, IsString, [27](#)
- SerreQuotientCategoryByCospansMorphism  
for IsCapCategory, IsCapCategoryMor-  
phism, IsCapCategoryMorphism, [28](#)  
for IsCapCategory, IsCapCategoryMor-  
phism, IsCapCategoryMorphism,  
IsCapCategoryMorphism, [27](#)  
for IsCapCategory, IsGeneralizedMorphism-  
ByCospan, [27](#)
- SerreQuotientCategoryByCospans-  
MorphismWithSourceAid  
for IsCapCategory, IsCapCategoryMor-  
phism, IsCapCategoryMorphism, [28](#)
- SerreQuotientCategoryBySpans  
for IsCapCategory, IsFunction, IsString, [28](#)
- SerreQuotientCategoryBySpansMorphism  
for IsCapCategory, IsCapCategoryMor-  
phism, IsCapCategoryMorphism, [29](#)

- for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, IsCapCategoryMorphism, 29
- for IsCapCategory, IsGeneralizedMorphismBySpan, 29
- SerreQuotientCategoryBySpansMorphismWithRangeAid
  - for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, 29
- SerreQuotientCategoryByThreeArrows
  - for IsCapCategory, IsFunction, IsString, 29
- SerreQuotientCategoryByThreeArrowsMorphism
  - for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, 30
  - for IsCapCategory, IsGeneralizedMorphismByThreeArrows, 30
- SerreQuotientCategoryByThreeArrowsMorphismWithRangeAid
  - for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, 30
- SerreQuotientCategoryByThreeArrowsMorphismWithSourceAid
  - for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, 30
- SerreQuotientCategoryMorphism
  - for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, 25
  - for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, IsCapCategoryMorphism, 25
  - for IsCapCategory, IsGeneralizedMorphism, 25
- SerreQuotientCategoryMorphismWithRangeAid
  - for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, 25
- SerreQuotientCategoryMorphismWithSourceAid
  - for IsCapCategory, IsCapCategoryMorphism, IsCapCategoryMorphism, 25
- SerreQuotientConversionFunctor
  - for IsCapCategory, IsCapCategory, 32
- SourceAid
  - for IsGeneralizedMorphismByThreeArrows, 18
- SubcategoryMembershipTestFunctionForSerreQuotient
  - for IsCapCategory, 26
- UnderlyingGeneralizedMorphism
  - for IsSerreQuotientCategoryMorphism, 27
- UnderlyingGeneralizedMorphismCategory
  - for IsCapCategory, 26
- UnderlyingGeneralizedObject
  - for IsSerreQuotientCategoryObject, 26
- UnderlyingHonestCategory
  - for IsCapCategory, 6, 26
- UnderlyingHonestObject
  - for IsGeneralizedMorphismCategoryByCospansObject, 9
  - for IsGeneralizedMorphismCategoryBySpansObject, 13
  - for IsGeneralizedMorphismCategoryByThreeArrowsObject, 18
  - for IsGeneralizedMorphismCategoryObject, 4
  - for IsSerreQuotientCategoryObject, 26