

PackageManager

**Easily download and install GAP
packages**

0.4

10 May 2019

Michael Torpey

Michael Torpey

Email: mct25@st-andrews.ac.uk

Homepage: <http://www-groups.mcs.st-andrews.ac.uk/~mct25/>

Address: School of Computer Science

University of St Andrews

Jack Cole Building, North Haugh

St Andrews, Fife, KY16 9SX

United Kingdom

Contents

- 1 Introduction** **3**
- 1.1 What does the PackageManager package do? 3
- 1.2 What does the PackageManager package not do? 3
- 1.3 A quick example 3

- 2 Commands** **4**
- 2.1 Installing and updating packages 4
- 2.2 Removing packages 7

- Index** **8**

Chapter 1

Introduction

1.1 What does the PackageManager package do?

This package provides the ability to install or remove a package using a single command: `InstallPackage` (2.1.1) or `RemovePackage` (2.2.1). The user can specify a package to install using its name, or using a URL to an archive, a repository, or a `PackageInfo.g` file. When installing, `PackageManager` also attempts to compile the package, and install the latest version of any required packages that are not already available.

1.2 What does the PackageManager package not do?

At present, `PackageManager` is fairly basic, without many of the advanced features available in package managers such as `pip` or `apt`. For instance, the user cannot install a particular version of a package, nor automatically update all packages. Removing a package will not remove any of its dependencies, since we do not track how packages were installed. When a package is installed, no tests are run to ensure that it is compatible with the installed version of GAP. Any of these features might be added in the future. Other feature requests can be posted on the issue tracker at <https://github.com/gap-packages/PackageManager/issues>.

1.3 A quick example

To install the latest deposited version of the Digraphs packages, use the following:

Example

```
gap> InstallPackage("digraphs");
```

To uninstall it later, use the following:

Example

```
gap> RemovePackage("digraphs");
```

`PackageManager` also supports version control repositories. To install the latest version of the `curlInterface` package from GitHub, use the following:

Example

```
gap> InstallPackage("https://github.com/gap-packages/curlInterface.git");
```

Chapter 2

Commands

2.1 Installing and updating packages

2.1.1 InstallPackage

▷ `InstallPackage(string[, interactive])` (function)

Returns: true or false

Attempts to download and install a package. The argument *string* should be a string containing one of the following:

- the name of a package;
- the URL of a package archive, ending in `.tar.gz` or `.tar.bz2`;
- the URL of a git repository, ending in `.git`;
- the URL of a mercurial repository, ending in `.hg`;
- the URL of a valid `PackageInfo.g` file.

The package will then be downloaded and installed, along with any additional packages that are required in order for it to be loaded. If this installation is successful, or if this package is already installed, `true` is returned; otherwise, `false` is returned.

By default, packages will be installed in user's home directory at `~/.gap/pkg`. Note that this location is not the default user `pkg` location on Mac OSX, but it will be created on any system if not already present. Note also that starting GAP with the `-r` flag will cause all packages in this directory to be ignored.

Certain decisions, such as installing newer versions of packages, will be confirmed by the user via an interactive shell - to avoid this interactivity and use sane defaults instead, the optional second argument *interactive* can be set to `false`.

To see more information about this process while it is ongoing, see `InfoPackageManager`.

Example

```
gap> InstallPackage("digraphs");  
true
```

2.1.2 UpdatePackage

▷ `UpdatePackage(name[, interactive])` (function)

Returns: true or false

Attempts to update an installed package to the latest version. The first argument *name* should be a string specifying the name of a package installed in the user GAP root (for example, one installed using `InstallPackage (2.1.1)`). The second argument *interactive* is optional, and should be a boolean specifying whether to confirm interactively before any directories are deleted (default value true).

If the package was installed via archive, the new version will be installed in a new directory, and the old version will be deleted. If installed via git or mercurial, it will be updated using `git pull` or `hg pull -u`, so long as there are no outstanding changes. If no newer version is available, no changes will be made.

Returns true if a newer version was installed successfully, or if no newer version is available. Returns false otherwise.

Example

```
gap> UpdatePackage("io");
#I io version 4.6.0 will be installed, replacing 4.5.4
#I Saved archive to /tmp/tm7r5Ug7/io-4.6.0.tar.gz
Remove old version of io at /home/user/.gap/pkg/io-4.5.4 ? [y/N] y
true
```

2.1.3 InfoPackageManager

▷ `InfoPackageManager` (info class)

Info class for the `PackageManager` package. Set this to the following levels for different levels of information:

- 0 - No messages
- 1 - Problems only: messages describing what went wrong, with no messages if an operation is successful
- 2 - Directories and versions: also displays informations about package versions and installation directories
- 3 - Progress: also shows step-by-step progress of operations
- 4 - All: includes extra information such as whether `curlInterface` is being used

Set this using, for example `SetInfoLevel(InfoPackageManager, 1)`. Default value is 3.

2.1.4 InstallPackageFromName

▷ `InstallPackageFromName(name[, interactive])` (function)

Returns: true or false

Attempts to download and install a package given only its name. Returns false if something went wrong, and true otherwise.

Certain decisions, such as installing newer versions of packages, will be confirmed by the user via an interactive shell - to avoid this interactivity and use sane defaults instead, the optional second argument *interactive* can be set to *false*.

2.1.5 InstallPackageFromInfo

▷ `InstallPackageFromInfo(info)` (function)

Returns: true or false

Attempts to download and install a package from a valid `PackageInfo.g` file. The argument *info* should be either a valid package info record, or a URL that points to a valid `PackageInfo.g` file. Returns true if the installation was successful, and false otherwise.

2.1.6 InstallPackageFromArchive

▷ `InstallPackageFromArchive(url)` (function)

Returns: true or false

Attempts to download and install a package from an archive located at the given URL. Returns true if the installation was successful, and false otherwise.

2.1.7 InstallPackageFromGit

▷ `InstallPackageFromGit(url [, interactive] [, branch])` (function)

Returns: true or false

Attempts to download and install a package from a git repository located at the given URL. Returns false if something went wrong, and true otherwise.

If the optional string argument *branch* is specified, this function will install the branch with this name. Otherwise, the repository's default branch will be used.

Certain decisions, such as installing newer versions of packages, will be confirmed by the user via an interactive shell - to avoid this interactivity and use sane defaults instead, the optional second argument *interactive* can be set to *false*.

2.1.8 InstallPackageFromHg

▷ `InstallPackageFromHg(url [, interactive] [, branch])` (function)

Returns: true or false

Attempts to download and install a package from a Mercurial repository located at the given URL. Returns false if something went wrong, and true otherwise.

If the optional string argument *branch* is specified, this function will install the branch with this name. Otherwise, the repository's default branch will be used.

Certain decisions, such as installing newer versions of packages, will be confirmed by the user via an interactive shell - to avoid this interactivity and use sane defaults instead, the optional second argument *interactive* can be set to *false*.

2.1.9 InstallRequiredPackages

▷ `InstallRequiredPackages()` (function)

Returns: true or false

Attempts to download and install the latest versions of all packages required for GAP to run. Currently these packages are GAPDoc, primgrp, SmallGrp, and transgrp. Returns `false` if something went wrong, and `true` otherwise.

Clearly, since these packages are required for GAP to run, they must be loaded before this function can be executed. However, this function installs the packages in the `~/.gap/pkg` directory, so that they can be managed by PackageManager in the future, and are available for other GAP installations on the machine.

2.2 Removing packages

2.2.1 RemovePackage

▷ `RemovePackage(name[, interactive])` (function)

Returns: true or false

Attempts to remove an installed package using its name. The first argument *name* should be a string specifying the name of a package installed in the user GAP root. The second argument *interactive* is optional, and should be a boolean specifying whether to confirm certain decisions interactively (default value true).

Returns true if the removal was successful, and false otherwise.

Example

```
gap> RemovePackage("digraphs");  
Really delete directory /home/user/.gap/pkg/digraphs-0.13.0 ? [y/N] y  
true
```

Index

InfoPackageManager, 5
InstallPackage, 4
InstallPackageFromArchive, 6
InstallPackageFromGit, 6
InstallPackageFromHg, 6
InstallPackageFromInfo, 6
InstallPackageFromName, 5
InstallRequiredPackages, 6

RemovePackage, 7

UpdatePackage, 5